



TECHNICAL DATA SHEET

BITUMEN UNDERCOATING SPRAY – forms a flexible coat that resists weather, weak acids and alkalis, as well as stone chip damage. The coat displays sound-proofing and sound-dampening properties. The product is a one- component formula that dries fast and exhibits good hiding power. **BITUMEN UNDERCOATING SPRAY** cannot be coated with other paint coats.

VOC II/B/e limit = 840 g/l VOC < 559 g/l.

SHELF LIFE 48 months/20°C

Vol. (ml)	Name	Article no.	Colour	units/pack.
500 Spray	Stonder Bitumen Spray	80109	Black	12



Degrease



Sand-paper




Degrease



Shake for 2 min.



Apply 3-4 coats



5-10 min.



60 min./20°C



Clean the valve for 5 s

SAFETY: See Safety Data Sheet.

OTHER INFORMATION

The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.

RAGS Ltd., Reg. No.: 40003133752, VAT number: LV40003133752

Legal address: Durbes street 8, Rīga, LV-1007,

Actual address: Džūkstes street 1, Rīga, LV-1004

Tel. [+371 67 808 780](tel:+37167808780), [+371 26 542 777](tel:+37126542777).