

baslac® Temperature Chart



baslac® non VOC clears

more than 2 panels	Hardener reducers	50-20	50-20	50-30	50-30
		60-20	60-30	60-30	60-40
up to 2 vertical panels	Hardener reducers	50-15	50-20	50-20	50-30
		60-10/20	60-10/20	60-20	60-30
up to one panel 1	Hardener reducers	50-15	50-15	50-20	50-20
		60-10/20	60-10/20	60-20	60-20
Spot repair	Hardener reducers			50-15	
				60-05	



baslac® Topcoat 30

more than 2 panels	Hardener reducers	50-20	50-20	50-30	50-30
		60-20	60-30	60-30	60-40
up to 2 vertical panels	Hardener reducers	50-15	50-20	50-20	50-30
		60-10/20	60-10/20	60-20	60-30
up to one panel 1	Hardener reducers	50-15	50-15	50-20	50-20
		60-10	60-10	60-20	60-20



baslac® 35

more than 2 panels	Reducer	60-20	60-30	60-40	60-40
up to 2 panels	Reducer	60-20	60-20	60-20	60-30
up to one panel 1 panel	Reducer	60-10	60-20	60-20	60-30



baslac primer filler

more than 1 panel	Hardener reducers	50-15	50-15	50-15	50-15
		60-10	60-20	60-20	60-20
up to 1 panel	Hardener reducers	50-10	50-15	50-15	50-15
		60-05/10	60-10	60-10	60-20
Spot repair	Hardener reducers			50-10	
				60-05/10	



°C



More information on
www.baslac.com